



Product Data Sheet	
7550-4035G	3' x 100' 11 Stake 100 gram 10' OC
7550-4100G	3' x 100' 13 Stake 100 gram 8' OC
7550-4105G	3' x 100' 13 Stake 100 gram 8' OC SOLID ORANGE
7550-4120G	3' x 100' 17 Stake 100 gram 6' OC

Silt Fence

100 Gram with 2" x 2" x 48" Stakes

Earthsavers DOT grade silt fence is made of 100% polypropylene woven fibers. Earthsavers meets or exceeds the properties listed below and is designed to meet most DOT and Federal Standards.

Properties	Test Method	MARV	
		English	Metric
Material		Woven Black Polypropylene & Wood Stakes	
Grab Tensile	ASTM D-4632	125 x 124 lbs	556 x 551.6 N
Grab Elongation	ASTM D-4632	15% x 15%	
CBR Puncture	ASTM D-6241	325 lbs	1,445.7 N
Trapezoid Tear	ASTM D-4533	65 x 65 lbs	289.1 x 289.1 N
Apparent Opening Size	ASTM D-4751	30 Sieve (0.023")	0.60 mm
Flow Rate	ASTM D-4751	10 gpm/ft ²	407.4 lpm/m ²
Permitivity	ASTM D-4491	0.1 Sec ⁻¹	
Ultraviolet Exposure	ASTM D-4355	70% after 500 Hours	

- Silt fence is a temporary sediment barrier designed to pond sediment-laden water and allow the sediment to fall out of suspension.
- Assembled in the USA.



Disclaimer: EarthSaver assumes no liability for the completeness or accuracy of this information. EarthSavers disclaims any and all implied, expressed or statutory standards, guarantees or warranties. This document should not be considered engineering advice. Always consult the project engineer for specific requirements. The end user assumes sole responsibility for the use of this information and product. The material property values listed above are subject to change without notice.

www.earth-savers.com

PO Box 2083 Woodland CA, 95776 • Toll Free (866) WATTLES • Fax (530) 668-5140