



ACF West is a D.B.A. for Northwest Geosynthetics Inc.
 2505 Frank Albert Rd E, Suite 111, Fife WA 98424 – PH: 253-922-6641 Fax: 253-922-6642

Description: ACF West “Supported” Silt Fence, ACF-WB48 uses a woven fabric attached with steel hog rings to galvanized steel support mesh.

Roll size: 48” fabric w/36” support mesh x 100 lineal foot
 Black Fabric

Fabric: The fabric, is a woven network of polypropylene fibers, stabilized to resist degradation due to ultraviolet exposure, and resistant to commonly encountered soil chemicals, mildew and insects. It is non-biodegradable and is stable within a ph range of 2-13. Manufactured for ACF West Inc. The fabric meets the following minimum average roll values (MARV):

Property	Test Method	MARV (English)
Grab Tensile	ASTM D 4632	124 x 124 lbs
Grab Elongation	ASTM D 4632	15% x 15%
Puncture	ASTM D 4833	75 lbs
Trapezoidal Tear	ASTM D 4533	70 x 70 lbs
UV Resistance	ASTM D 4355	70% @ 500hr
AOS	ASTM D 4751	40 sieve
Permittivity	ASTM D 4491	0.1 sec ⁻¹

Support Mesh: 14ga. Galvanized utility mesh, 4’ x 2” opening, 36” height, 100’ length